

CRASH RATED BOOM BARRIER - GAJRAJ 4

Swaraj Secutech presents India's first indigenously designed and manufactured Crash Rated Boom Barrier. The barrier has been impact rated in accordance with IWA 14-1:2013 std at Horiba MIRA, U.K. wherein barrier stopped a 7.2 ton truck @ 48 km/h with only 0.5 meter penetration.

The crash beam incorporates a design protected high tensile carbon steel which on collision transmits the kinetic energy through the crash beam to the reinforced foundation. All parts of the barriers are manufactured keeping in mind the corrosive nature of the tropical Indian Climate and are corrosion proof.

The barrier can be operated manually in times of power failure or automatically by using an optional accumulator.



SAFETY AGAINST ACCIDENT:

Safety during operation has been most important to us and we provide dual safety mechanism when the barrier is operated automatically.

- 1. Safety against vehicle: loop detector
- 2. Safety against human traffic: photo sensor

INDIA

Survey No. 1427, Chhatral-Mehsana Highway, Rajpur Jhulasan Road, Dharpura Chokdi, Jhulasan- 382705, Ahmedabad. (T) +91 88826 64055, Email - <u>info@swarajsecutech.com</u>, Website: <u>www.swarajsecutech.com</u>

UAE

Swaraj Secutech Equipment & Machinery Trading LLC, Warehouse-1, Plot No 1228. Sector 5, New Industrial Area, Umm Al Thaoob, UAQ, UAE (T) +971 508641797, Email: <u>rashid@swarajsecutech.com</u> Website: <u>www.swaraj.ae</u>

NORTH AMERICA

MIRΔ

Swaraj Secutech Canada INC 2300 Yonge street, 1600, Toronto, ON, M4P 1E4 (T) +1 (647) 242-6738 Email: <u>mona@swarajsecutech.com</u>,



SPECIFICATION

MODEL NO.	GAJRAJ 4
PRODUCT RATING	IWA 14-1:2013 Gate V/7200[N2A]/48/90:0.5
RATED IMPACT ENERGY	673.9 KILO JOULES
BARRIER TYPE	CRASH RATED BOOM BARRIER
MECHANISM	ELECTRO-HYDRAULIC / MANUAL
RATED LENGTH	6 METERS
RATED HEIGHT	900MM
OPERATING TEMPERATURE	-30 DEGREE TO +65 DEGREE CELSIUS
POWER SUPPLY (AUTOMATIC)	415 V (AC), 50 HZ / 220V AC , 60HZ
OPERATING PRESSURE (AUTOMATIC)	PRESSURE IN THE OIL PUMP CAN BE ADJUSTED BETWEEN 30 TO 120 BARS
SPEED	6-8 SECONDS
OPERATIVE OPTIONS	PUSH BUTTON / REMOTE CONTROL / MANUAL
PROTECTION CLASS	IP 68
MTBF	5 MILLION CYCLES
IN CASE OF POWER FAILURE	MANUAL OPERATION POSSIBLY BY HAND PUMP / BYPASS VALVE
MATERIAL OF CONSTRUCTION	HIGH TENSILE CARBON STEEL
DUTY CYCLE	100%
SAFETY MECHANISM	SENSORS FOR HUMAN AND VEHICULAR SAFETY IS PROVIDED AS A STANDARD ACCESSORY ALONG WITH VISUAL AND AUDIBLE WARNING LAMP
ACTIVATED WARNING LIGHTS (OPTIONAL)	ACTIVATED WARNING LIGHTS WHILE BARRIER IS IN OPERATION
ADDITIONAL FEATURES	 THE HYDRAULIC POWER-PACK CAN BE INSTALLED WITHIN THE MAIN BARRIER BODY OR CAN BE SEPARATELY INSTALLED IN CASE OF SPACE CONSTRAINT PAIR OF PHOTO SENSORS AND LOOP DETECTOR WILL BE PROVIDED AS STANDARD ACCESSORIES FOR SAFETY AGAINST HUMAN TRAFFIC AND VEHICLES

INDIA

Survey No. 1427, Chhatral-Mehsana Highway, Rajpur Jhulasan Road, Dharpura Chokdi, Jhulasan- 382705, Ahmedabad. (T) +91 88826 64055, Email - <u>info@swarajsecutech.com</u>,

Website: <u>www.swarajsecutech.com</u>

"PROUDLY MADE IN INDIA"

UAE

Swaraj Secutech Equipment & Machinery Trading LLC, Warehouse-1, Plot No 1228. Sector 5, New Industrial Area, Umm Al Thaoob, UAQ, UAE (T) +971 508641797, Email: <u>rashid@swarajsecutech.com</u> Website: <u>www.swaraj.ae</u>

NORTH AMERICA

Swaraj Secutech Canada INC 2300 Yonge street, 1600, Toronto, ON, M4P 1E4 (T) +1 (647) 242-6738 Email: <u>mona@swarajsecutech.com</u>,